

ST-625 THERMOPTEK SMOKE ALARM

Sensor type	Thermoptek Multi-Sensor
Battery type	2 x 1.5v AA alkaline batteries



- Thermoptek Multi-Sensor technology as used by over 90% of the UK Fire and Rescue Services.
- 2 year warranty.
- Large central button - test / Smart Silence.
- Easy to install with automatic battery engagement on base plate.
- Smart Silence - allows the alarm to be silenced for up to 10 minutes in the event of a known false alarm. During these 10 minutes if additional smoke is detected the alarm will sound.
- Sleep Easy - allows a low battery chirp to be silenced for 8 hours, this function can be used up to 10 times.



Technical Specification

Dimensions	107mm (diameter) x 34mm (depth)	
Supply voltage	3V DC	
Battery	x2 AA	
Technology	Thermoptek	
Alarm sound level	85dB(A) at 3m (minimum)	
Installation positions	Ceiling / Wall	
Operating temperature	+4°C to +38°C	
Operating humidity	Up to 90% RH non-condensing	
Storage temperature	-20°C to +60°C	
Storage humidity	Up to 93% RH non-condensing	
Plastic material	ABS, UL94 VO fire retardant	
Warranty	2 years	
Weight	157g	
Certified to	BS EN 14604:2005	
Independently tested to	N/A	
Maximum number of connected units	N/A	
Operating frequency	N/A	
Range	N/A	