

FA6115-INT 10 YEAR SMOKE ALARM - Optical, 5 Year Replaceable Battery

Sensor type	Optical
Battery type	2 x AA Alkaline Replaceable Batteries (Included)



- Battery powered optical smoke alarm
- Reduces nuisance cooking alarms
- Large central test button
- Sleep Easy silence the low battery chirp for 8 hours
- Operating Light (RED) flashes approximately every 40 seconds confirming alarm is powered
- Low Battery Warning 'beeps' approximately every 40 seconds when the battery needs replacing
- Loud 85 Decibel Piezo Electric Alarm
- Suitable for leisure accommodation vehicles (LAV)
- Easy Installation fixings supplied
- Quiet test function supports discreet testing at a lower volume when compared to standard alarms

Technical Specification





| 1110 | 10032 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033 | 10033

Dimensions	118.1mm (diameter) x 31.5mm (depth)
Battery	2 x AA Alkaline Replaceable Batteries (Included)
Sensor Technology	Optical
Alarm sound level	85dB(A) at 3m (minimum)
Installation positions	Wall/Ceiling
Operating temperature	+4°C to +38°C
Operating humidity	Up to 90% RH (non condensing)
Storage temperature	-20°C to +60°C
Storage humidity	Up to 93% RH (non condensing)
Warranty	5 Years
Certified to	EN 14604:2005+AC:2008
Weight	185g
Leisure Accomodation Vehicles	Yes